



M587EMD41LED2840-W

ARTEMIS (DOB) recessed round super comfort downlight, Medium light distribution, 10-cm Dia., 4000K, LED2, 700 Lumens, 10W, White



About Product

ARTEMIS modern recessed round super comfort (Darklight) downlight luminaire is designed and manufactured by Megalite in various sizes for modern office and commercial lighting applications. Durability, UV free, excellent visual comfort, energy saving, glare control, environment friendliness, and higher than 80 color rendering index (CRI) are among the highlights of this luminaire.



Technical Information

Luminaire Name:	ARTEMIS
Catalog Code/product code:	M587EMD41LED2840-W
Mounting Type:	Recessed-Gypsum false ceiling, Recessed-Concealed false ceiling, Recessed-Exposed false ceiling
Application:	Shopping centers, Gallery and museum, Hospitality
Light source type:	DOB LED (PF> 0.9)
Module/ Lamp quantity:	1
CCT (Color temperature):	4000K - Neutral White
Light source:	LED
LED Module brand name:	Edison
Lumen maintenance:	> 50.000 hours
Lumen maintenance factor:	L70
CRI (Color rendering index):	> 80
Power Consumption:	10
Luminous Flux:	700
Efficacy (lm/W):	70
IP (Ingress Protection):	IP43 (Underside)
Insulation Class:	Class I
Max. Ambient Temperature:	35
Mains voltage:	198~253 VAC


M587EMD41LED2840-W
ARTEMIS (DOB) recessed round super comfort downlight, Medium light distribution, 10-cm Dia., 4000K, LED2, 700 Lumens, 10W, White

Voltage Frequency:	50/60 Hz
Wire cross section:	0.5
Terminal material:	Polyamide
Terminal Spec:	Cable looping is possible. Tool free wire connection. 3-Pole (Size: 2.5)
Cable Looping:	Yes
Body Material:	Die-Cast aluminum
Body Coating:	Powder coated
Body Color:	White
RAL:	RAL9003
Body Characteristic:	Specially designed cooling feature
Reflector Material:	aluminum sheet
Reflector Coating:	Pre-anodized
Diffuser/Glass Material:	Polycarbonate
Diffuser/Glass Shape:	Frosted
Diffuser/Glass Characteristic:	Uniform light distribution
Light Distribution:	35 degrees
Clamp Material:	Stainless steel
Clamp Characteristic:	Easy and safe tool free installation of the luminaire
Packaging type:	Nylon cover and carton
Weight(Kg):	0.3
Dimensions(mm):	Ø118x97
Order Option (Routine option):	5700K color temperature

M587EMD41LED2840-W

ARTEMIS (DOB) recessed round super comfort downlight, Medium light distribution, 10-cm Dia., 4000K, LED2, 700 Lumens, 10W, White

Photometric Graph



Glare Evaluation According to UGR												
p Ceiling		70	70	50	50	30	70	70	50	50	30	30
p Walls		50	30	50	30	30	50	30	50	30	30	30
p Floor		20	20	20	20	20	20	20	20	20	20	20
Room Size X Y		Viewing direction at right angles to lamp axis					Viewing direction parallel to lamp axis					
2H	2H	-15.2	-14.6	-15.0	-14.4	-14.2	-15.2	-14.6	-15.0	-14.4	-14.2	-14.2
	3H	-15.4	-14.8	-15.1	-14.5	-14.3	-15.4	-14.8	-15.1	-14.5	-14.3	-14.3
	4H	-15.4	-14.9	-15.1	-14.6	-14.4	-15.4	-14.9	-15.1	-14.6	-14.4	-14.4
	6H	-15.5	-15.0	-15.2	-14.7	-14.4	-15.5	-15.0	-15.2	-14.7	-14.4	-14.4
	8H	-15.5	-15.1	-15.2	-14.8	-14.5	-15.5	-15.1	-15.2	-14.8	-14.5	-14.5
4H	12H	-15.6	-15.1	-15.2	-14.8	-14.5	-15.6	-15.1	-15.2	-14.8	-14.5	-14.5
	2H	-15.4	-14.9	-15.1	-14.6	-14.4	-15.4	-14.9	-15.1	-14.6	-14.4	-14.4
	3H	-15.6	-15.1	-15.2	-14.8	-14.5	-15.6	-15.1	-15.2	-14.8	-14.5	-14.5
	4H	-15.6	-15.3	-15.3	-14.9	-14.6	-15.6	-15.3	-15.3	-14.9	-14.6	-14.6
	6H	-15.7	-15.4	-15.3	-15.0	-14.7	-15.7	-15.4	-15.3	-15.0	-14.7	-14.7
8H	8H	-15.8	-15.5	-15.4	-15.1	-14.7	-15.8	-15.5	-15.4	-15.1	-14.7	-14.7
	12H	-15.8	-15.6	-15.4	-15.2	-14.7	-15.8	-15.6	-15.4	-15.2	-14.7	-14.7
	4H	-15.8	-15.5	-15.4	-15.1	-14.7	-15.8	-15.5	-15.4	-15.1	-14.7	-14.7
	6H	-15.9	-15.6	-15.4	-15.2	-14.8	-15.9	-15.6	-15.4	-15.2	-14.8	-14.8
	8H	-15.9	-15.7	-15.4	-15.3	-14.8	-15.9	-15.7	-15.4	-15.3	-14.8	-14.8
12H	12H	-16.0	-15.8	-15.5	-15.3	-14.9	-16.0	-15.8	-15.5	-15.3	-14.9	-14.9
	4H	-15.8	-15.6	-15.4	-15.2	-14.7	-15.8	-15.6	-15.4	-15.2	-14.7	-14.7
	6H	-15.9	-15.7	-15.4	-15.3	-14.8	-15.9	-15.7	-15.4	-15.3	-14.8	-14.8
	8H	-16.0	-15.8	-15.5	-15.3	-14.9	-16.0	-15.8	-15.5	-15.3	-14.9	-14.9
	12H	-16.0	-15.8	-15.5	-15.3	-14.9	-16.0	-15.8	-15.5	-15.3	-14.9	-14.9
Variation of the observer position for the luminance distances S												
S = 1.0H		+5.3 / -10.6					+5.3 / -10.6					
S = 1.5H		+8.0 / -87.1					+8.0 / -87.1					
S = 2.0H		+10.0 / -85.1					+10.0 / -85.1					
Standard table		BK00					BK00					
Correction Summand		-14.1					-14.1					
Corrected Glare Indices referring to 700lm Total Luminous Flux												

Dimensional Drawing

